



MOBILE FALL PROTECTION

BTS AirHook Max PRO Trailer Electric / Hydraulic Fall Arrest Trailer

BTS AirHook Max PRO Trailer

At an anchor point height of 15mts (49.4 ft), the AirHook Max PRO Trailer is the tallest mobile overhead fall protection anchor rated for 4-workers. With a total weight of approx. 2.4T (2.6 ton), the AirHook Max Pro Trailer is designed to be towed for use in both on-road and off-road work environments



MOBILE FALL PROTECTION



BTS AirHook Max PRO Trailer Electric / Hydraulic Fall Arrest Trailer

BTS AirHook Max PRO Trailer

PRODUCT FEATURES

- Four (4) single user anchor points rated system.
- Maximum overhead anchor point height of 15m (49.2 ft) and with two 2m (6.5 ft) offset arms that can rotate 360° independently.
- Self-contained 12v Electric/hydraulic system.
- Set-up and anchor height adjusting is carried out with simple push button controls.
- 4 stage telescopic mast, adjustable to 15m anchor point height.
- Mast retracts down effortlessly onto the trailer and is securely held in place.
- Takes 10 minutes to set-up for use and a similar amount of time to lower the unit after use.
- Equipped with electric/hydraulic brakes and a independent break-away system.
- The main mast is raised and lowered using an electric (DC) hydraulic pump and valve assembly with built-in hose burst protection reducing any manual handling issues on-site.
- Equipped with manual override to lowering the mast in case of power failure.
- High performance deep cycle battery with built in solar pannels and mains power battery charger also charges whilst connected to a suitably wired towing vehicle.
- Lockable toolboxes for safe storage of equipment such as harnesses and fall arrestors.
- Multiple fork lift pockets for ease of lifting and storing when shipping equipment around the countryside. Optionally can be fitted with rated lifting points, and self-levelling jacks.
- Heavy duty off road construction for use in rugged and harsh work environments.
- Equipped with safety features including lockable Isolation switch, warning beacon, warning alarm and emergency stop.
- Accessories: Inertia Reels and Inertia Reels with Self Rescue Capability.
- Full size spare wheel as standard.
- 12v wide beam work lights.

Specifications

Code	70728
Ultimate Strength Rating:	4x 12kN (2,700 lbs) anchor points Tested (statically and dynamically)
Capacity (Fall Arrest):	Max. 4 workers weighing not more than 140kg (310 lbs) each
Allowable MAF/AAF for SRL/SRD:	6 kN (1350 lbs)
Height:	Adjustable from 6.1m (20.0 ft) to 15m (49.4 ft)
Reach:	2m (6.5 ft)
Foot print:	L: 4.9m (16.0 ft) x W: 2.2m (7.2 ft) x H: 1.9m (6.2 ft)
Weight:	2.4T (2.6 ton)
Anchorage type:	Limited Free Fall Arrest

